

# SIGNAL CONDITIONERS



FP90-1, field mount flow transmitter, \$408, shown larger than actual size.

- ✓ Permanent and Resettable Totalizers
- ✓ Scalable Outputs
- ✓ Relay Options
- ✓ Mounting Versatility
- ✓ Simulate Function
- ✓ 2 x 16 Character Dot Matrix LCD
- ✓ Chemical Resistant Enclosure and Self-Healing Window
- ✓ Large Pushbuttons
- ✓ Clearly Marked Terminal Labels Application
- ✓ Flow Control and Monitoring
- ✓ Filtration or Softener Regeneration
- ✓ Effluent Totalization
- ✓ Pump Protection
- ✓ Feed Pump Pulsing
- ✓ Ratio Control
- ✓ Water Distribution
- ✓ Leak Detection

FP90 Series Starts at

**\$408**



The FP90 Series flow transmitter is an advanced solution that converts the signal from many flow sensors into a 4 to 20 mA signal for long distance transmission. Configuration flexibility is maximized with two optional relays for process control, two packaging options for integral/pipe mount or panel installation, and scalability for virtually any flow range or engineering unit. State-of-the-art electronic design ensures long-term reliability, signal stability, and simple user setup and operation. The FP90 can be integrally mounted to FP8500 Series paddlewheel sensors utilizing a mounting kit.

The FP90 can be remotely used with the OMEGA® FP-5100, FP-5200, FP-5300, FP-5060, FP-2541, FP-5600, FP-3-1500 or FP-6000 flow sensors and an FP90UM mounting kit. The FP90-XP units are designed to be panel mounted. The three front keys control all programming and scaling of the FP90—there are no pots to tweak or internal adjustments to make. Simply enter the K-factor and the FP90 displays rate with field-adjustable decimal point, mA output value, total (field selectable for resettable or non-resettable operation) and the date of the last reprogramming. The 8-digit alphanumeric LCD shows every program step in clear language, allowing display in any engineering units and timebase in seconds, minutes, hours or days. A special pushbutton sequence permits entry into the programming, thus providing security against unauthorized reprogramming.

## SPECIFICATIONS

**Compatibility:** Flow Sensors with frequency outputs

**Accuracy:** ±0.5% of reading @ 25°C

**Enclosure**

**Rating:** NEMA 4X (IP65) front

**Case:** PBT

**Window:** Polyurethane coated polycarbonate

**Keypad:** Sealed 4-key silicone rubber

**Weight:** Approx. 325 g (12 oz)

**Display:** Alphanumeric 2 x 16 LCD

**Update Rate:** 1 second

**Contrast:** User selected, 5 levels

**Environmental**

**Operating Temperature:**

-10 to 70°C (14 to 158°F)

**Storage Temperature:**

-15 to 80°C (5 to 176°F)

**Relative Humidity:**

0 to 95%, non-condensing

**Standards and Approvals**

CSA, CE, UL listed

**Electrical**

**Sensor Input:**

**Range:** 0.5 to 1500 Hz

**Sensor Power:**

**2-Wire:** 1.5 mA @ 5 Vdc ±1%

**3 or 4 Wire:** 20 mA @ 5 Vdc ±1%

Optically isolated from current loop short circuit protected

**Current Output:** 4 to 20 mA, isolated, fully adjustable and reversible

**Power:** 12 to 24 Vdc ±10%, regulated

**Max Loop Impedance:**

50 Ω max @ 12 V, 325 Ω max @ 18 V,

600 Ω max @ 24 V

**Update Rate:** 100 ms

**Accuracy:** ±0.03 mA

**Relay Output:** Mechanical SPDT

contacts: Hi, Lo, Pulse, Off

**Maximum Voltage Rating:**

5 A @ 30 Vdc, 5 A @ 250 Vac

resistive load

**Hysteresis:** User adjustable;

max 300 pulses/min

**Open-Collector Output:**

Hi, Lo, Pulse, Off Open-collector,

optically isolated, 50 mA max, sink,

30 Vdc max pull-up voltage.

Max 300 pulses/min

Recommended Reference Book:  
Flow Measurement Methods &  
Applications, **CM-4339, \$145.**

See Section Y for Additional Books



FP8501 paddlewheel flow sensor, \$226, shown actual size.



FP90-2P flow transmitter, \$483, shown actual size.

### Accessories

**MOST POPULAR MODELS HIGHLIGHTED!**

Model No.	Price	Description
FP90UM	\$50	Universal mounting kit for remote wall or pipe mount
FP90-4X	45	NEMA 4X rear cover (panel mount)
FP90IM	50	Integral mounting kit for mounting on top of FP85XX sensors
FP90RC	17	RC filter (for relay use)

**Standard Paddlewheel Sensors (1 fps minimum) for integral mounting (requires FP90IM integral mounting hardware and OMEGA fitting) ±0.2 fps accuracy**

Model No.	Price	Description
FP8501	\$226	½ to 4" pipe, polypropylene body/titanium shaft
FP8502	244	5 to 8" pipe, polypropylene body/titanium shaft
FP8503	449	½ to 4" pipe, PVDF body/Hastelloy C shaft

**Low flow paddlewheel sensors (0.3 fps minimum) for integral mounting (requires FP90IM integral mounting hardware and OMEGA fitting) ±0.1 fps accuracy**

Model No.	Price	Housing Material	Shaft Material	Rotor	Pipe Size
FP8501A	\$249	Polypropylene	Titanium	Black PVDF	0.5 to 4"
FP8502A	268	Polypropylene	Titanium	Black PVDF	5 to 8"
FP8503A	471	Natural PVDF	Hastelloy C	Natural PVDF	0.5 to 4"

**MOST POPULAR MODELS HIGHLIGHTED!**

## To Order (Specify Model Number)

Model No.	Price	Description	Mounting	Output(s)
FP90-1	\$408	Flow transmitter	Field mount*	4 to 20 mA and open collector output
FP90-2	483	Flow transmitter	Field mount*	4 to 20 mA and dual relays
FP90-3	692	Flow transmitter, dual input	Field mount*	4 to 20 mA and dual open collector outputs
FP90-1P	408	Flow transmitter	Panel mount	4 to 20 mA and open collector output
FP90-2P	483	Flow transmitter	Panel mount	4 to 20 mA and dual relays
FP90-3P	692	Flow transmitter, dual input	Panel mount	4 to 20 mA and dual open collector outputs

Comes complete with operator's manual.

\* Field mount transmitters require FP90IM internal mounting kit for FP8500 or FP8500A sensor or FP90UM for all other compatible sensors.

**Ordering Examples:** FP90-1 field mount flow transmitter, FP90IM integral mounting kit, FP8501A paddlewheel sensor, FP-5310 installation fitting for 1" PVC pipe, \$408 + 50 + 249 + 165 = \$872.

FP90-1 field mount flow transmitter and OCW-3, OMEGACARE<sup>SM</sup> extended warranty program, \$408 + 102 = \$510.

OMEGACARE<sup>SM</sup> extended warranty program is available for models shown on this page. Ask your sales representative for full details when placing an order. OMEGACARE<sup>SM</sup> covers parts, labor and equipment loaners.

# omega.co.uk<sup>®</sup>

Your One-Stop Source for Process Measurement and Control!

Freephone 0800 488 488 | International +44(0) 161 777 6622 | Fax +44(0) 161 777 6622 | Sales@omega.co.uk

[www.omega.co.uk](http://www.omega.co.uk)



#### UNITED STATES

[www.omega.com](http://www.omega.com)

1-800-TC-OMEGA  
Stamford, CT.

#### CANADA

[www.omega.ca](http://www.omega.ca)

Laval(Quebec)  
1-800-TC-OMEGA

#### GERMANY

[www.omega.de](http://www.omega.de)

Deckenfronn, Germany  
0800-8266342

#### UNITED KINGDOM

[www.omega.co.uk](http://www.omega.co.uk)

Manchester, England  
0800-488-488  
+44-(0)161-777-6611

#### FRANCE

[www.omega.fr](http://www.omega.fr)

0800-466-342

#### BENELUX

[www.omega.nl](http://www.omega.nl)

0800-099-33-44



## More than 100,000 Products Available!

### • Temperature

Calibrators, Connectors, General Test and Measurement Instruments, Handheld Instruments for Temperature Measurement, Ice Point References, Indicating Labels, Crayons, Cements and Lacquers, Infrared Temperature Measurement Instruments, Recorders, Relative Humidity Measurement Instruments, PT100 Probes, PT100 Elements, Temperature & Process Meters, Timers and Counters, Temperature and Process Controllers and Power Switching Devices, Thermistor Elements, Probes and Assemblies, Thermocouples, Thermowells and Head and Well Assemblies, Transmitters, Thermocouple Wire, RTD Probes

### • Flow and Level

Air Velocity Indicators, Doppler Flowmeters, Level Measurement, Magnetic Flowmeters, Mass Flowmeters, Pitot Tubes, Pumps, Rotameters, Turbine and Paddle Wheel Flowmeters, Ultrasonic Flowmeters, Valves, Variable Area Flowmeters, Vortex Shedding Flowmeters

### • pH and Conductivity

Conductivity Instrumentation, Dissolved Oxygen Instrumentation, Environmental Instrumentation, pH Electrodes and Instruments, Water and Soil Analysis Instrumentation

### • Data Acquisition

Communication Products and Converters, Data Acquisition and Analysis Software, Data Loggers Plug-in Cards, Signal Conditioners, USB, RS232, RS485, Ethernet and Parallel Port Data Acquisition Systems, Wireless Transmitters and Receivers

### • Pressure, Strain and Force

Displacement Transducers, Dynamic Measurement Force Sensors, Instrumentation for Pressure and Strain Measurements, Load Cells, Pressure Gauges, Pressure Reference Section, Pressure Switches, Pressure Transducers, Proximity Transducers, Regulators, Pressure Transmitters, Strain Gauges, Torque Transducers, Valves

### • Heaters

Band Heaters, Cartridge Heaters, Circulation Heaters, Comfort Heaters, Controllers, Meters and Switching Devices, Flexible Heaters, General Test and Measurement Instruments, Heater Hook-up Wire, Heating Cable Systems, Immersion Heaters, Process Air and Duct, Heaters, Radiant Heaters, Strip Heaters, Tubular Heaters