# **MINIATURE COMPRESSION LOAD CELL** WITH THREADED CENTER HOLE

LC321 Series **Compression** LC321-750, \$480, shown actual size. 1/4-28 UNF THRU All Models .50 (38) MADE IN analab NIST USA Technical 516 (13) DIA. .031 Books Force (.79)Available 🎙 **Online!** Robotic Applications, 38 mm (1.5") Diameters 40 (10)books1.com nega.co for Easy Installation WIRING CODE 1.5 m (5') 4-CONDUCTOR SHIELDED CABLE GREEN +OUTPUT WHITE -OUTPUT RED +INPUT Provided Dimensions: mm (in) **BLACK - INPUT** 

> Safe Overload: 150% of capacity Ultimate Overload: 300% of capacity Input Resistance: 360 Ω minimum Output Resistance: 350  $\pm 5 \Omega$

Construction: Stainless steel

Electrical: 1.5 m (5') 4-conductor shielded cable

ΜΛΩΤ ΡΛΡΙΙΙ ΛΕ ΜΛΠΕΙ Ο ΗΙΩΗΙ ΙΩΗΤΕΠΙ

			FUFULAN			
To Order <i>(Specify Model Number)</i>						
CAPACITY						
lb	kg	MODEL NO.	PRICE	COMPATIBLE METERS*		
250	114	LC321-250	\$480	DPiS, DP41-S, DP25B-S		
500	227	LC321-500	480	DPiS, DP41-S, DP25B-S		
750	341	LC321-750	480	DPiS, DP41-S, DP25B-S		
1000	455	LC321-1K	480	DPiS, DP41-S, DP25B-S		
2000	909	LC321-2K	480	DPiS, DP41-S, DP25B-S		

Comes with 5-point NIST-traceable calibration. \* See section D for compatible meters. Ordering Examples: LC321-250, 250 lb capacity subminiature compression load cell, \$480. LC201-1K, 1000 lb capacity subminiature compression load cell, \$480.

#### VULLEGOUDA

ACCECCONI			
MODEL NO.	PRICE	DESCRIPTION	
ME-1804	\$125	Reference Book: Mechanical Design Handbook	

0-250 lb to 0-2000 lb 0-114 kg to 0-909 kg 1 Newton = 0.2248 lb

1 daNewton = 10 Newtons 1 lb = 454 g1 t = 1000 kg = 2204 lb

- Miniature Package for
- Threaded Center Hole
- ✓ 5-Point Calibration
- Ultra-Low Profile

OMEGA's LC321 Series compression load cells offer a broad load range, a threaded center hole, and an ultra-low profile for easy installation. Their all stainless steel construction and rugged design ensure long life and high reliability in industrial environments.

#### SPECIFICATIONS Output: 2 mV/V

Excitation: 10 Vdc, 15 Vdc max Accuracy: ±2.0% FSO linearity. hysteresis, repeatability combined 5-Point Calibration: 0%, 50%, 100%, 50%, 0%

Zero Balance: ±2% FSO **Operating Temp Range:** -54 to 121°C (-65 to 250°F)

**Compensated Temp Range:** 16 to 71°C (60 to 160°F)

Thermal Effects: Zero: 0.005% FSO/°F Span: 0.010% rdg/°F Protection Class: IP65

# omega.co.uk®

Your One-Stop Source for Process Measurement and Control!

Freephone 0800 488 488 | International +44(0) 161 777 6622 | Fax +44(0) 161 777 6622 | Sales@omega.co.uk

## www.omega.co.uk



UNITED STATES www.omega.com 1-800-TC-OMEGA Stamford, CT.

CANADA www.omega.ca Laval(Quebec)

1-800-TC-OMEGA

#### GERMANY

www.omega.de Deckenpfronn, Germany 0800-8266342 UNITED KINGDOM www.omega.co.uk Manchester, England 0800-488-488 +44-(0)161-777-6611

> FRANCE www.omega.fr 0800-466-342

BENELUX www.omega.nl 0800-099-33-44



# More than 100,000 Products Available!

### Temperature

Calibrators, Connectors, General Test and Measurement Instruments, Handheld Instruments for Temperature Measurement, Ice Point References, Indicating Labels, Crayons, Cements and Lacquers, Infrared Temperature Measurement Instruments, Recorders, Relative Humidity Measurement Instruments, PT100 Probes, PT100 Elements, Temperature & Process Meters, Timers and Counters, Temperature and Process Controllers and Power Switching Devices, Thermistor Elements, Probes and Assemblies, Thermocouples, Thermowells and Head and Well Assemblies, Transmitters, Thermocouple Wire, RTD Probes

### Flow and Level

Air Velocity Indicators, Doppler Flowmeters, Level Measurement, Magnetic Flowmeters, Mass Flowmeters, Pitot Tubes, Pumps, Rotameters, Turbine and Paddle Wheel Flowmeters, Ultrasonic Flowmeters, Valves, Variable Area Flowmeters, Vortex Shedding Flowmeters

### pH and Conductivity

Conductivity Instrumentation, Dissolved Oxygen Instrumentation, Environmental Instrumentation, pH Electrodes and Instruments, Water and Soil Analysis Instrumentation

## Data Acquisition

Communication Products and Converters, Data Acquisition and Analysis Software, Data Loggers Plug-in Cards, Signal Conditioners, USB, RS232, RS485, Ehernet and Parallel Port Data Acquisition Systems, Wireless Transmitters and Receivers

### • Pressure, Strain and Force

Displacement Transducers, Dynamic Measurement Force Sensors, Instrumentation for Pressure and Strain Measurements, Load Cells, Pressure Gauges, Pressure Reference Section, Pressure Switches, Pressure Transducers, Proximity Transducers, Regulators, Pressure Transmitters, Strain Gauges, Torque Transducers, Valves

### Heaters

Band Heaters, Cartridge Heaters, Circulation Heaters, Comfort Heaters, Controllers, Meters and Switching Devices, Flexible Heaters, General Test and Measurement Instruments, Heater Hook-up Wire, Heating Cable Systems, Immersion Heaters, Process Air and Duct, Heaters, Radiant Heaters, Strip Heaters, Tubular Heaters